

SPLITTER UHF

- UHF BAND 470-860 MHz
- Special version with unequal power splitting
- Pressurizable on request



← IN 7/8" OUT 2 7/8"



IN 7/8" OUT 4 7/8" ↑

TYPICAL SPECIFICATIONS

Impedance	50 Ohm
Frequency Range	470-860 MHz
VSWR	<1.05 in each frequency range
Insertion Loss	0.05 dB Max
RF-Connectors	Female N, DIN 7/16, or EIA-flange 7/8", 1+5/8", 3+1/8", 4+1/2", 6+1/8"
Max Power Input	According to depending on connectors
Number of outputs	2-8 (In according to the model.)
Length approx.	Approx. 550 mm
Diameter external tube	From 40 to 120 mm In according to the working power
Mounting	With special pipe clamp
Working Temperature	-20°C ÷ +50°C
Colour	Enamel Gray Ral 7001
Materials	Aluminium, Brass, Copper, PTFE, Stainless steel, Silvering (min 12µm thickness)



← IN 7/8" OUT 6 7/8"



← IN 7/8" OUT 6 7/16"

EXAMPLES OF SPLITTERS

SPECIALS VERSIONS	
BAND	LENGHT
Band I 47-88 MHz	Approx. 2400 mm
Band III 174-230 MHz	Approx. 850 mm
Band IV V 470-860 MHz	Approx. 550 mm

