

SPLITTER FM

- **FM BAND 87.5÷108 MHz**
- **Special version with unequal power splitting**
- **Pressurizable on request**
- **Option Clamps (minimum 2 for Splitter)**

TYPICAL SPECIFICATIONS

Impedance	50 Ohm
Frequency Range	87.5-108 MHz
VSWR	1.05:1 Max
Insertion Loss	0.05 dB Max
Connectors	N-7/16"-7/8"-1+5/8"-3+1/8"-4+1/8" In according to the working power
Max Power Input	From 100 Watts to 40 KW In according to the model
Number of outputs	2-8 (In according to the model)
Length approx.	1600 mm
Diameter external tube	From 40 to 120 mm In according to the working power
Mounting	With special pipe clamp
Working Temperature	-20°C ÷ +50°C
Colour	Enamel gray ral 7001
Materials	Aluminium, Brass, Copper, PTFE, Stainless Steel, Silvering (min 12µ thickness)



IN 7/8" OUT 4 7/8" ↑

IN 1+5/8" OUT 2 7/8" ↑



↑ IN 3+1/8" OUT 2 3+1/8"



↑ IN 3+1/8" OUT 4 1+5/8"



IN 1+5/8" OUT 8 7/8" →



← IN 1+5/8" OUT 4 7/16"

EXAMPLES OF SPLITTERS

"These specifications are subject to change without notice"